ALLOWANCE EQUIPAGE LIST (AEL)

EQUIPAGE NOMENCLATURE/CHARACTERISTICS	T	MANUAL		1	TIE10.1	T(01)			_		
				IDENTIFICATION NO.		NO.	DATE			PAGE	
CODA DO SE CUIDADADA MAD MAD ANA SE COLOR		TECHNICAL DOCUMENT									
SCBA, DC-FF SHIPBOARD FOR MHC-51 CLASS	NUMBER										
		PLAN		1							
	<u> </u>			2 - 33	<u> 3002</u>	241	15	06	-24 <i>-</i>	03	. 1
HARACTERISTICS				<u> </u>	ON BOAF			RD ALLOWANCE			TABLE
THIS AEL IS TO REPLACE THE OBA AND OBA CANIS			E O M RP N S C U A EP O T C R C S T O C								_,
REQUIREMENTS CURRENTLY FOUND ON DAMAGE CONTRO			C U A ER O T O C C C N O R E C C C C V C C C C C C C C C C C C C C	COL.	COL.	COL.	COL.	COL.	COL. C	OL.	COL.
2-880044200 SERIES AND BREATHING APRS-OXY	A4 ALL		LE FVC S YUA Y	1	2	3	4	5	6	7	8
2-930094060 THRU 2-930094064.	\ UCE6										
THE SELF-CONTAINED BREATHING APPARATUS (SCBA	) USES ,	A TO									
HIGH PRESSURE AIR CYLINDER WITH A REGULATOR									İ	ĺ	
SUPPLY BREATHING AIR TO THE USER DURING DAI				<b>H</b> 1					-		
AND FIRE FIGHTING FUNCTIONS. IT SHALL HAVE RATED SERVICE TIME OF THIRTY MINUTES AND FO	A MINII	7UM 4.5									
MINUTES (DEPENDING ON THE SIZE OF THE INSTA			\$ 166 H N UNS								
CYLINDERS).	MLLEU A	T L	e in the second						- 1		
THE SCBA AND ITS ASSOCIATED CHARGING EQUIPME	ит (мит	rн									
INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRE	SSUBSI	GII									
CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR (	CYL INDFI	R IN						ļ	- 1		
A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS, FACE											
THE SELF-CONTAINED BREATHING APPARATUS (SCBA) USES A HIGH PRESSURE AIR CYLINDER WITH A REGULATOR RATED TO SUPPLY BREATHING AIR TO THE USER DURING DAMAGE CONTROL AND FIRE FIGHTING FUNCTIONS. IT SHALL HAVE A MINIMUM RATED SERVICE TIME OF THIRTY MINUTES AND FORTY-FIVE MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS). THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS, FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: SCBA (30 MIN CARBON) 99AO10025 SCBA (45 MIN CARBON) 99AO10026											
FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING A	PLS:										
SCBA (30 MIN CARBON) 99A01											
SCBA (45 MIN CARBON) 99A01	0026					1	,				
ALL CHANGES TO THIS AEL MUST BE ENDORSED BY	THE TYC	MC					i				
AND APPROVED BY NAVSEA DAMAGE CONTROL. IN I	WRITING						1				
NOTE 1: THE SELF-CONTAINED BREATHING APPARAT	US (SCB.	<b>A</b> )									
CAN BE RECONFIGURED TO EITHER A 30 MI		DR									
45 MINUTE RATING BY EXCHANGING THE C					- 1						
INSTALLED IN THE SCBA BACKPACK. THE					- 1						
CONFIGURATION CHANGE WILL BE CONTROL	LED BY	THE								i	
THE SELF-CONTAINED BREATHING APPARATUS (SCBA) USES A HIGH PRESSURE AIR CYLINDER WITH A REGULATOR RATED TO SUPPLY BREATHING AIR TO THE USER DURING DAMAGE CONTROL AND FIRE FIGHTING FUNCTIONS. IT SHALL HAVE A MINIMUM RATED SERVICE TIME OF THIRTY MINUTES AND FORTY-FIVE MINUTES (DEPENDING ON THE SIZE OF THE INSTALLED AIR CYLINDERS).  THE SCBA AND ITS ASSOCIATED CHARGING EQUIPMENT (WHICH INCLUDES DIESEL AND/OR ELECTRIC AIR COMPRESSORS) CONSISTS OF HIGH PRESSURE (4500 PSIG) AIR CYLINDER IN A BACKPACK TYPE HARNESS. AIR PRESSURE REGULATORS, FACE MASK AND ASSOCIATED AIR HOSEE. FOR REPAIR PARTS SUPPORT SEE THE FOLLOWING APLS: SCBA (30 MIN CARBON) SCBA (45 MIN CARBON) 99AO10025 SCBA (45 MIN CARBON) 99AO10025 SCBA (45 MIN CARBON) ALL CHANGES TO THIS AEL MUST BE ENDORSED BY THE TYCOM AND APPROVED BY NAVSEA DAMAGE CONTROL, IN WRITING. NOTE 1: THE SELF-CONTAINED BREATHING APPARATUS (SCBA) CAN BE RECONFIGURED TO EITHER A 30 MINUTE OR 45 MINUTE RATING BY EXCHANGING THE CYLINDER INSTALLED IN THE SCBA BACKPACK. THE SCBA CONFIGURATION CHANGE WILL BE CONTROLLED BY THE DCA OR CHENG, HOWEVER, THE NUMBER OF 30 MINUTE OR 45 MINUTE CYLINDERS ONBOARD CANNOT EXCEED THE QUANTITIES DEFINED WITHIN THIS AEL. THE NUMBER AND SIZE OF CYLINDERS ONBOARD CANNOT EXCEED THE QUANTITIES DEFINED WITHIN THIS AEL. THE NUMBER AND SIZE OF CYLINDERS IS DETERMINED BY ADDING CYLINDERS WITHIN AN SCBA AND SPARE CYLINDER QUANTITIES LISTED ON THIS AEL. NOTE 2: BREATHING AIR REDUCING STATION (BARS), ONE PER SHIP; STOWAGE DETERMINED BY DCA. COLUMNS 1 THRU 7 BLANK COLUMNS 8 FOR MHC-51 SHIP CLASS ONLY CAGE-12004											
					1						
QUANTITIES DEFINED WITHIN THIS AEL. THE NUMBER AND SIZE OF CYLINDERS IS DETERMINED BY ADDING										1	
CYLINDERS WITHIN AN SCBA AND SPARE C	DI ADDI	¥13			- 1			ļ		ļ	
QUANTITIES LISTED ON THIS AEL.	TLINDER										
NOTE 2: BREATHING AIR REDUCING STATION (BARS	)				- 1			İ		Ì	
ONE PER SHIP; STOWAGE DETERMINED BY	ρςΑ				ļ					i	
COLUMNS 1 THRU 7 BLANK	23/1.										
COLUMN 8 FOR MHC-51 SHIP CLASS ONLY					1				- 1		
CAGE-12004					- 1						
CCF DATE -12 02											
804861-37 BREATHE APRS, 30MIN CARB	N 9Z 42	40-01-486-1946	<u>UPA<b>00</b>0 1</u> EEA								24
REFERENCE NO./DESCRIPTIVE DATA ITEM NAME		STOCK NO.	S COMMON AND AND AND AND AND AND AND AND AND AN	1	2	3	4	5	6	7	8
										T	
ALLOWANOE FOUR	IDACE I	IOT (AEL)	C C N V S S C				ŀ				
ALLOWANCE EQU	IPAGE L	JOI (AEL)		2 - :	3300	024	115	06-	- 24 -	03	1
SHIP TYPE & HULL NO.										$\Box$	

ALLOWANCE EQUIPAGE LIST (AEL)

FOURDACE MOMENTO ATUDE/OUADAGTERIOTICS	*****		JUIPAGE LIST (A								
EQUIPAGE NOMENCLATURE/CHARACTERISTICS			MANUAL		IDENTIA	CATIC	ON NO.	DA.	ΤE		PAGE
SCBA, DC-FF SHIPBOARD FOR	MHC-51 CLASS	TECHNICAL DOCUMENT NUMBER	PLAN								
					2-330024115			06-24-03		2	
CHARACTERISTICS				s s				RD ALLOWANCE			TABLE
				S S N E P T O O O O O O O O O O O O O O O O O O			H. COL			COL.	COL.
6314781	BREATHING AIR RED STA AY SEE NOTE 2	9Z 42	40-01-485-7705	UPAQUO ILAY	1	2 3	1-4-	5	6	7	1
804871-31	CYLINDER, 30MIN CARBON FACEPIECE, SZ SM FACEPIECE, SZ X-LRG	9Z 42 9Z 42	40-01-486-1939 40-01-449-3106 40-01-449-3120 N D	UPAOZZ 15EA 16EA 16EA 16EA							72 4 2 2
REFERENCE NO/DESCRIPTIVE DATA	ITEM NAME		STOCK NG								
TIE CHENCE NO DESCRIPTIVE DATA	HEM NAME		STOCK NO.	S M RS N CUI Q T	1	2 3	4	5	6	7	8
SHIP TYPE & HULL NO.	ALLOWANCE EQUI	PAGE L	-IST (AEL)	S O O O O O O O O O O O O O O O O O O O	2-33	3002	4115	06	-24-	-03	2